

Google scholar

(table OR map) "segregated fit" (allocation OR

Search

[Advanced Scholar Search](#)

Scholar

Articles and patents

anytime

include citations

[Create email alert](#)

Results 1 - 10 of about 76. (0.36 sec)

Did you mean: (table OR map) "segregated fit" (**allocator** OR allocator)

The memory fragmentation problem: Solved?

[psu.edu](#) (PDF)MS Johnstone, PR Wilson - ACM SIGPLAN Notices, 1999 - [portal.acm.org](#)

... This **allocator** is a **segregated fit** algorithm with 128 size classes. ... **Table 2:** Maximum number of live objects per size class ... hand-optimized memory **allocation**, because a well-designed **allocator** should usually be able to do as well as or better than most programmers' hand ...

[Cited by 139](#) - [Related articles](#) - [BI Direct](#) - [All 21 versions](#)

TLSF: A new dynamic memory allocator for real-time systems

[upv.es](#) (PDF)M Masmano, I Ripoll, A Crespo, J Rea - 16th Euromicro Conference ... - [ieeexplore.ieee.org](#)

... that Doug Lea's **allocator** [6], which implements a good-fit policy (a nearly best-fit based on a **segregated fit** policy), performs ... It is also possible that the **allocator** relies on the underlying OS (or the hardware MMU) to request new memory areas to ... First **allocation** requests are ...

[Cited by 52](#) - [Related articles](#) - [All 7 versions](#)

Memory allocation with lazy fits

[psu.edu](#) (PDF)Y Chung, SM Moon - ... of the 2nd international symposium on ..., 2000 - [portal.acm.org](#)

... A backup **allocation** with a **segregated fit** when **allocation** with a pointer increment fails, on ... fitting algorithms would be used even more in- frequently than in **table 6**. Since ... Lea's memory **allocator** implementation uses something sim- ilar to pointer incrementing **allocation** in order ...

[Cited by 12](#) - [Related articles](#) - [BI Direct](#) - [All 12 versions](#)

Implementation of a constant-time dynamic storage allocator

[psu.edu](#) (PDF)M Masmano, I Ripoll, J Rea, A ... - Software: Practice ..., 2008 - [interscience.wiley.com](#)

... 16], the authors presented a new **allocator** called TLSF (two-level **segregated fit**) and compared ...

Temporal requirements: The primary requirement for any real-time **allocator** is to provide allo ...

The worst-case execution time (WCET) of memory **allocation** and deallocation has to be ...

[Cited by 12](#) - [Related articles](#) - [All 4 versions](#)

[HTML] Magazines and vmem: Extending the slab allocator to many CPUs and arbitrary resources

[usernix.org](#) (HTML)J Bonwick, J Adams - [usernix.org](#)

... If the **map** ever gets more fragmented than that, the **allocator** throws away resources ... allocated segments (white) are also linked into an allocated-segment hash **table**, and boundary ... This

approach, called **segregated fit**, actually approximates best-fit because any segment on the ...

[Cited by 30](#) - [Related articles](#) - [Cached](#) - [All 9 versions](#)

[\[PDF\] Dynamic storage allocation for real-time embedded systems](#)

[psu.edu](#) [PDF]

M Masmano, I Ripoll, A Crespo - Proceedings of the Real-Time Systems ..., 2003 - Citeseer

... The basic **segregated fit** mechanism uses an array of free lists, with each array holding free blocks within a ... search sequence is as follows: 1.- calculate the "f" and "s" indexes (using the **map**-ping function) ... An algorithm with constant execution time for dynamic storage **allocation**. ...

[Cited by 8](#) - [Related articles](#) - [View as HTML](#) - [All 11 versions](#)

[Dynamic memory management for embedded real-time systems](#)

[psu.edu](#) [PDF]

A Crespo, I Ripoll, M Masmano - From Model-Driven Design to Resource ..., 2006 - Springer

... TLSF (Two Level **Segregated Fit**) is a new **allocator** has been designed specifically to meet real-time constraints. ... **Table 2**. Fragmentation worst-case ... problem is a problem of "poor" **allocator** implementations rather than an intrinsic characteristic of the **allocation** problem itself A ...

[Cited by 6](#) - [Related articles](#) - [All 15 versions](#)

[A comparison of memory allocators for real-time applications](#)

M Masmano, I Ripoll, A Crespo - ... on Java technologies for real-time ..., 2006 - portal.acm.org

... TLSF (Two-Level **Segregated Fit**) [11] is a bounded-time, good-fit **allocator**. ... **Table 1**: Algorithm complexity **Allocation** Deallocation First-fit/Best-fit $O(H \cdot 2M)$ $O(1)$ Binary-buddy $O(\log^2(H \cdot M))$ $O(\log^2(H \cdot M))$ DLalloc $O(H \cdot M)$ $O(1)$ Half-fit $O(1)$ $O(1)$ TLSF $O(1)$ $O(1)$...

[Cited by 10](#) - [Related articles](#) - [All 2 versions](#)

[Efficient system-level prototyping of power-aware dynamic memory managers for embedded systems](#)

[psu.edu](#) [PDF]

D Aienza, S Mamagkakis, F Poletti, JM ... - INTEGRATION, the VLSI ..., 2006 - Elsevier

... This example is depicted in Fig. 3. Thus, we can merge the two **allocation** heaps saving memory footprint because the memory can be reused for both. ... For the results shown in Figs. 5, 8, and

Table 2, we use the View the MathML source technology node. ...


[Cited by 10](#) - [Related articles](#) - [All 14 versions](#)

[A high-performance memory allocator for memory intensive applications](#)

JM Chang, Y Hasan, WH Lee - hpc, 2000 - computer.org

... process is much efficient than splitting process which is used in conventional **segregated fit** algorithms ... The different **allocation** bits used enable free() to differentiate between pre-allocated chunks to be ... Next **table** provides a summary of the size of the tested programs (in terms of ...

[Cited by 5](#) - [Related articles](#) - [All 4 versions](#)

 [Create email alert](#)

Did you mean to search for: [\(table OR map\) "segregated fit" \(allocator OR allocator\)](#)



Result Page: 1 2 3 4 5 6 7 8 [Next](#)

(table OR map) "segregated fit" (allocation OR allocator)

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2010 Google